

GEN TO BS EN
50525-2-11
VDE0250



PVC İZOLELİ VE KILIFLI, ÇOK TELLİ KONTROL KABLOŞU

PVC INSULATED AND SHEATHED, FLEXIBLE CONTROL CABLES

YY KONTROL KABLOŞU | YY CONTROL CABLE



TEKNİK VERİLER / TECHNICAL DATA

Cu/PVC/PVC

RoHS'a Uygun (RoHS Compliant)

Nominal Kesit
mm²
Nominal Cross
Section mm²

Yaklaşık Dış
Çap mm
Overall
Diameter mm
approximately

Yaklaşık Net
Ağırlık kg/km
Net Weight kg/km
approximately

İletken Direnci Max.
ohm/km(20°C)
Conductor DC
Resistance at (20°C)
max. ohm/km

Akım Taşıma Kapasitesi
Current Carrying Capacity in
Havada (A)
Air (A)

YSLY (300/500 V)

Nominal Kesit mm ²	Yaklaşık Dış Çap mm	Yaklaşık Net Ağırlık kg/km	İletken Direnci Max. ohm/km(20°C)	Akım Taşıma Kapasitesi Havada (A)
2x2,5	7,6	99	7,98	25
3x2,5	8,3	127	7,98	25
4x2,5	9,0	158	7,98	20
5x2,5	10,3	203	7,98	19,5
6x2,5	11,4	248	7,98	19,5
7x2,5	11,4	263	7,98	16,3
8x2,5	13,5	342	7,98	16,3
10x2,5	16,3	471	7,98	13,8
12x2,5	15,8	481	7,98	13,1
14x2,5	16,5	541	7,98	12,5
16x2,5	17,4	607	7,98	12,5
18x2,5	18,3	677	7,98	12,5
19x2,5	18,3	692	7,98	11,3
24x2,5	21,4	914	7,98	10,0
25x2,5	21,4	929	7,98	10,0
30x2,5	24,4	1173	7,98	9,40
36x2,5	25,2	1310	7,98	9,40
3x4	10,4	203	4,95	34
4x4	11,4	254	4,95	34
5x4	12,5	310	4,95	34
7x4	13,8	400	4,95	-
12x4	21,7	860	4,95	-
2x6	11,2	224	3,30	51
3x6	11,7	248	3,30	43
4x6	13,1	354	3,30	43
5x6	14,9	451	3,30	43
6x6	16,2	540	3,30	43
7x6	16,2	577	3,30	-
12x6	24,9	1194	3,30	-
3x10	15,5	474	1,91	59
4x10	17,0	594	1,91	60
5x10	18,7	729	1,91	-
7x10	20,4	934	1,91	-
3x16	17,9	683	1,21	79
4x16	19,7	864	1,21	80
5x16	21,6	1057	1,21	80
5x25	26,9	1609	0,780	101
4x25	25,1	1344	0,780	101
3x35	25,0	1395	0,554	129
4x35	27,4	1762	0,554	126
5x35	30,0	2135	0,554	126